

C-2300B, NEW Multi conductor cable for all cameras:

Features:

Small, rugged, bright green.
Replaces the C-1500, C-2000, C-2300 and C5500 CABLES.

Mechanical:

Braided Kevlar strength member (1200 lbs.).
Lengths to 3000 ft.
Material: NEON Green Polyurethane jacket.
Temp. rating -40 to +90C.
Diameter .360"
38 lbs.(17.5Kg) per 500 ft.

Electrical:

Conductors: 16 #22 awg and 1 mini RG-59 coax.
300 volt rated conductors.

Options:

Lengths to 3000 ft.



C-3100, Neutrally Buoyant,:

Features:

Neutrally Buoyant, bright green.
Multi conductor cable for all cameras

Mechanical:

Braided Kevlar strength member (1000 lbs.).
Standard length 500 ft
Material: Neon Green Foam Polyurethane jacket.
Diameter .55".
50 lbs.(22.7Kg) per 500 ft.

Electrical:

Conductors: 75 ohm coax, 1 #24 awg tsp, 1 #24awg tp,
3 #18 awg, 2 #22awg
300 volt rated conductors.

Options:

C-3101, 500ft. Cable assembly for all Cameras and Lights.
C-3105, 500ft. Cable assembly for ROV.



C-3400, Neutrally Buoyant cable for the Outland 1000 ROV:

Features:

Neutrally Buoyant, bright green.
Multi conductor cable for the Outland 1000 ROV

Mechanical:

Conductors: Cat5e Lan Cable (4 TP #24), 12 #22 AWG.
Braided Kevlar strength member (1000 lbs).
Standard length 500 ft.
Material: Neon Green Foam Polyurethane jacket.
Diameter .55".
50 lbs.(22.7Kg) per 500 ft.

Electrical:

Conductors: Cat5e Lan Cable (4 TP #24), 12 #22 AWG.
300 volt rated conductors.

Options:

C-3401, 500ft. Cable assembly for Outland 1000 ROV.
C-3410, 1000ft. Cable assembly for Outland 1000 ROV.

