

- INTERNAL
- PAN/TILT
- ZOOM/FOCUS
- COLOR
- 10-1 OPTICAL ZOOM



**USES INCLUDE: ROV, LAUNCH CAGE, DROP CAMERA, TOW SLED, ETC.**

**MECHANICAL:**

- Length..... 6 in. (150mm)  
(excluding connector)
- Diameter..... 6 in. (150mm)
- Weight..... Dry 4 LBS. (1.8kg)  
Wet .6 LBS. (.27kg)
- Depth Rating..... 3300 ft. (1000 m)
- Housing.....6061-T6 Anodized Aluminum

**ELECTRICAL:**

- Image Device.....1/4" CCD Sensor  
Color , 768 H x 494 V, Pixels
- Sensitivity..... Color 1 lux.
- Resolution.....Color 470 Horz. lines.
- PWR..... (12-24 VDC) @ 280 ma.

**OPTICAL:**

- Lens..... Auto-Iris, 4.2-42mm F1.8
- Housing port..... Acrylic
- Pan/Tilt Speed..... Approx. 35 deg./sec.

**CONNECTOR:**

Standard Connector..... XSK-7-BCL  
(Mate is RMK-7-FS)

**OPTIONS:**

1. CCIR (PAL) Format.
2. Customer specified connector.
3. Long Line Video Amplifier
4. RS-485, Digital camera control.
7. Heaters for temp below 40 deg. F. (1.3 amps.)