

• **HALOGEN BULB**



MODEL#	UWL-100	UWL-200
MECHANICAL:		
1. Diameter.....	2.375 (60mm)	1in to 1.6 in. max.(25-40mm)
2. Length.....	3.25 in (81mm) (excluding connector)	3.0 in. (75mm)
3. Weight.....	(Dry) 1 lb. (.45kg) (Wet) .8 lb.(.36kg)	10.5 oz. (.3kg) 8 oz.(.23kg)
4. Depth Rating.....	3300 ft. (1000m)	3300 ft. (1000m)
5. Housing.....	Anodized AL.	17-4, Stainless
6. Port/Globe.....	Pyrex	Borosilicate Glass
7. Connector.....	SEM3P-S4	GRE3P-S4
Mating Connector.....	RMG-3-FS	RMG-3-FS
ELECTRICAL:		
1. Voltage.....	up to 120 V Max.	up to 120 V Max.
2. Wattage.....	250 max.	150 Max.
3. Bulb.....	Std. Q250cl/mc	std. Q150cl/mc
OPTIONS:		
1. Reflector.....	Wide angle or Standard	NA
2. Bulbs.....	75 to 250 watt	75 to 150 watt

(Specifications subject to change without notice.)

NOTE: Outland recommends the use of an Isolation transformer or Ground Fault Interrupter (GFI), with lamps above 30 Volts.