


Cable Reel

- **WATERPROOF IP68 SLIP RING DESIGN**
- **DURABLE CONSTRUCTION**
- **PORTABLE SUITCASE DESIGN WITH WHEELS**



MECHANICAL SPECIFICATIONS:

External Width	23.53 in. (597.6 cm)
External Length	32.96 in. (837.2 cm)
External Height (Closed)	18.87 in. (479.4 cm)
Weight (without cable)	49 lbs. (22.23 kg)
Fixed Topside Whip Length	20 feet (6 m)
Waterproof rating	IP68
Operation Temps	-20°C to +80°C
Max Rotational Speed	250 rpm
Crank Handle	Included

REEL DIMENSIONS:

Traverse Length	25.69 in. (50.3 cm)
Fill Diameter	17.25 in. (38.74 cm)
Barrel Diameter	8.5 in. (21.6 cm)

SLIP RING ELECTRICAL SPECIFICATIONS:

Voltage Rating	400VDC
Power Current Rating	6A per conductor
Number of Power Conductors	5
Data Current Rating	2A per conductor
Number of Data Conductors	4 twisted pairs

REEL CAPACITY:

Tether Diameter	Max Tether Length
0.625 (15.875 mm)	750 ft (229 m)
0.55 in (13.97 mm)	1000 ft (305 m)

OPTIONS:

(Customer Specified Connector)