


- ZOOM/FOCUS
- SD OR HD COLOR
- 10x OPTICAL ZOOM
- COMPACT SIZE



USES INCLUDE: ROV, LAUNCH CAGE, DROP CAMERA, TOW SLED, ETC.

**MECHANICAL:**

Diameter..... 2.5 in. (63.5 mm)  
 Length (excluding connector)..... 5.0 in. (127 mm)  
 Weight in air..... 1.0 lb. (0.45 kg)  
 Weight in seawater..... 2 oz. (0.06 kg)  
 Depth Rating..... 1,500 ft. (460 m)  
 Housing Material..... Delrin  
 Port Material..... Acrylic

**CAMERA PROPERTIES:**

SD Image Device..... 1/4 in. Color CCD Sensor  
 (1020 H x 508 V pixels)  
 HD Image Device (type AHD)..... 1/2.9 in. Color 1080P  
 (1920x1080 pixels)  
 Sensitivity..... 0.2 lux  
 Resolution..... SD 700TVL, HD 1080P  
 Zoom..... 10:1 optical  
 Focus..... Auto or manual  
 Standard Format..... NTSC


**ELECTRICAL:**

Input Voltage..... 12-30 VDC  
 Power..... 300 mA @ 12 VDC

**CONNECTOR:**

Standard Connector..... XSK-5-BCL  
 Mate for Standard Connector..... RMK-5-FS

1. Video
2. Ground / Common
3. Power (+)
4. Com +
5. Com -



Looking at the male pins on the back of the camera

**OPTIONS:**

1. High Definition 1080P Camera
2. CCIR (PAL) Format
3. Deep Water Aluminum Housing, 3,280 ft (1000m)
4. Connector Options