



## **UWL-401**

- EQUIVALENT TO 150 WATT HALOGEN
- CAN OPERATE IN WATER OR AIR
- 24 VDC, 20 WATTS
- 2,500 LUMENS





**TOP VIEW** 



FRONT VIEW

### APPLICATIONS INCLUDE: UNDERWATER CAMERA OR WORK LIGHTS

#### **MECHANICAL:**

Diameter	1.62 in. (41 mm)
Length (excluding connector)	4 in. (102 mm)
Weight in air	0.48 lbs. (0.22 kg)
Weight in seawater	0.18 lbs. (0.08 kg)
Depth Rating	6,560 ft. (2000 m)
Housing Material	
Port Material	Glass

#### **ELECTRICAL:**

Input Voltage	24 VDC
Dower	20 Watts (Typical)
Analog Dimming	24VDC to 0VDC (0% to 100%)
Light Full on at 0 VD	C control and Full off at 24 VDC

#### **LIGHT PROPERTIES:**

Light Output	1,100 lux @ 1 m
(2,500 lumens; Equiv. to	
Color Temperature	3,000 K
Beam Angle	100 degrees

#### CONNECTOR:

Standard Connector	11-0004
Mate for Standard Connector	RMG-3-FS

1. Power (+)

- 2. Power Return / Common
- 3. 0-24 VDC Control

# n antrol

#### **OPTIONS:**

- RS485 Digital dimming control
- Connector options