




- **WATERPROOF SLIP RING DESIGN**
- **QUICK RELEASE CRANK ARM**
- **DURABLE CONSTRUCTION**
- **BALL BEARING SLIP RING**



## OVERALL SPECIFICATIONS:

|                         |                     |
|-------------------------|---------------------|
| Width                   | 22.5 in. (57 cm)    |
| Length                  | 22.5 in. (57 cm)    |
| Height (without wheels) | 21.2 in. (54 cm)    |
| Weight (without cable)  | 42.5 lbs. (19.3 kg) |

## REEL DIMENSIONS:

|                 |                    |
|-----------------|--------------------|
| Traverse Length | 15.9 in. (40.4 cm) |
| Fill Diameter   | 19.0 in. (48 cm)   |
| Barrel Diameter | 8.4 in. (21.3 cm)  |

## DIVE CABLE (C-2300C):

|                       |                     |
|-----------------------|---------------------|
| Cable Diameter        | 0.38 in. (9.7 mm)   |
| Total Length Capacity | ~2039 ft. (621.5 m) |
| Cable Weight          | ~155 lbs. (70.5 kg) |
| Total Weight          | ~198 lbs. (90 kg)   |

## ROV CABLE (C-3400):

|                       |                    |
|-----------------------|--------------------|
| Cable Diameter        | 0.55 in. (14 mm)   |
| Total Length Capacity | 850 ft. (259 m)    |
| Cable Weight          | 85 lbs. (38.6 kg)  |
| Total Weight          | 130 lbs. (59.1 kg) |

## OPTIONS:

1. Customer Specified Connector
2. Case Wheels